

TECHFIN RESIN CURE

Petroleum Resin Based Concrete Curing Compound

Petroleum resin based concrete curing compound, composed of high-grade petroleum resin extracts in a solution of quick drying solvents. Provides a high curing efficiency for concrete substrates.

BENEFITS:



Economical single application



Reduces incidence of hairline cracks



Efficient curing. Applicable to all site placed concrete

APPLICATIONS

Techfin Resin Cure retains moisture in fresh concrete which is essential to ensure adequate strength development and to minimize initial shrinkage crack development. Consequently, the concrete has a harder, dust free surface whilst hairline cracks are reduced to a minimum.

DIRECTIONS

Techfin Resin Cure should be applied to freshly cast concrete surfaces as evenly as possible. For horizontal surfaces, Techfin Resin Cure should be applied immediately after the initial surface sheen has disappeared. In the case of formed concrete, Techfin Resin Cure should be applied immediately after the removal of formwork (while the concrete is still green). To assist breakdown of the Techfin Resin Cure on vertical and formed surfaces, it is essential to dampen down the concrete with clean water prior to application. Breakdown of the Techfin Resin Cure film

TECHNICAL DETAILS

Appearance	Light amber liquid
Film Finish	Light amber tack free
Coverage	8 m ² / L
Drying Time	2 hrs
Packaging	25 L & 200 L drums
Techfin Resin Cure is supplied in 25 & 200 L drums.	

starts after 30 days and can take up to 6 months to degrade completely.

WATCH POINTS

- Techfin Resin Cure is not a coating system and may yellow with age.
- Remove Techfin Resin Cure prior to any subsequent surface finish application.
- Clean all equipment well after use.

WARRANTY

Technical Finishes products are manufactured under high quality standards and are warranted against defective materials and are sold subject to standard Terms and Conditions of Sale, copies of which can be obtained upon request. Technical Finishes deals with approved applicators and carry a back to back warranty with these clients. Technical Finishes cannot be held responsible for the workmanship in surface preparation and application of our products, it is understood that the approved contractor will guarantee such workmanship and application. It is vital that the application is done in accordance to our specification.