

SOLIDKOTE DECKSEAL

Single Pack Wood Sealer



An easy to use, water-based UV protected acrylic specifically designed to protect and seal outdoor timber decks, wooden cabins or furniture.

Breathable sealer that will not blister off. Available in clear or different wood colours.

UNIQUE PRODUCT BENEFITS

- Non-toxic, water based with no toxic solvents.
- Environmentally friendly - no smell.
- Tough and flexible.
- UV resistant, long lasting, excellent adhesion to all timber.
- Easily applied.
- Fast drying - 3 coats in a day.
- Re-coatable.
- Translucent colours allowing natural grain of timber to show through.
- Natural, satin finish.

TECHNICAL DETAILS

Application	Roller
Finish	Satin / Gloss
Application Temperature	10 to 30°C
Recommended Coats	3 to 4 coats
Dry Film Thickness	50 microns / coat
Colour	Clear, Mahogany, Bali Brown, Imbuia, Oregon
Walk on Time	18 hrs @ 20°C
Full Cure	3 Days
Primer	Lignoprime



SUBSTRATE REQUIREMENTS

Timber surfaces to be coated must be clean and free of dust.

APPLICATION

New timber must be free of wax, or mill glaze residue. Remove by solvent wiping. Sand new timber with 120 grit paper. Apply minimum 3 coats at 10 – 14 m² / coat depending on porosity or type of wood. Allow minimum 2 hours between coats. This can vary depending on temperature and humidity. Do not coat in damp conditions or late afternoon where dew can form on the timber.

Leading manufactures of specialist epoxy and polyurethane flooring systems, specialised construction and corrosion protection products.

Distribution facilities nationwide

Western Cape
+27 (0)21 535 4455

Eastern Cape
+27 (0)41 451 3944

Gauteng
+27 (0)11 822 7242

KwaZulu-Natal
+27 (0)31 705 7733



info@technicalfinishes.com • www.technicalfinishes.com



TECHNICAL FINISHES
SPECIALIST FLOORING AND CONSTRUCTION SOLUTIONS

HEALTH AND SAFETY

This system is non-hazardous to your health and the environment.

Please read Safety Data Sheet and specific health and safety data for this product provided in compliance with the requirements of OHS Act No.85 of 1993. The finished system is not hazardous to health or the environment.

WARRANTY

Technical Finishes products are manufactured under high quality standards and are warranted against defective materials and are sold subject to standard Terms and Conditions of Sale, copies of which can be obtained upon request. Technical Finishes deals with approved applicators and carry a back to back warranty with these clients. Technical Finishes cannot be held responsible for the workmanship in surface preparation and application of our products, it is understood that the approved contractor will guarantee such workmanship and application. It is vital that the application is done in accordance to our specification.

***Leading manufactures of specialist epoxy and polyurethane flooring systems,
specialised construction and corrosion protection products.***

Distribution facilities nationwide

Western Cape

+27 (0)21 535 4455

Eastern Cape

+27 (0)41 451 3944

Gauteng

+27 (0)11 822 7242

KwaZulu-Natal

+27 (0)31 705 7733



TECHNICAL FINISHES
SPECIALIST FLOORING AND CONSTRUCTION SOLUTIONS



info@technicalfinishes.com • www.technicalfinishes.com