# **SOLIDKOTE 401**

General Purpose Clear, Low Viscosity
Penetrating Epoxy Sealer or Laminating Resin

A liquid structural epoxy, medium viscosity, two component epoxy used in general construction and flooring applications. Excellent glass fiber laminating epoxy for structural uses.

## **UNIQUE PRODUCT BENEFITS**

- Excellent chemical resistance
- · Excellent mechanical and physical properties
- Solvent-free, low viscosity and excellent adhesion on concrete

#### **APPLICATIONS:**

- Used for rigid concrete crack injection, encapsulating or casting compound
- Can be used to saturate, seal and strengthen surfaces such as wooden boats
- Can be used for glass fiber laminating epoxy
- Excellent concrete primer
- Excellent high build clear coat


## SUBSTRATE REQUIREMENTS

Surfaces to be coated must be clean and free of dust, oily residues and loose friable material. All surfaces to be suitably prepared using diamond grinders to remove laitance. The substrate should dry to 75% RH (BS8204). Moisture readings on concrete must be less than 5%.

#### **INSTALLATION:**

This is a specialized reactive epoxy resin that must be used in accordance with its physical performance criteria. Consult Technical Finishes technical department for further advise.

TECHNICAL DETAILS	
Compressive Strength	> 80 MPa
Tensile Strength	> 50 MPa
Elongation	> 3%
Application	By roller or brush, applying the coats wet on wet until fully absorbed
Mix Ratio	2:1
Pot Life	25 min @ 20°C
Colour	Clear
Application Temperature	10 to 30°C
Service Temperature	60°C max (dry)
Practical Cure	18 hrs
Full Cure	7 days at 20°C



Leading manufactures of specialist epoxy and polyurethane flooring systems, specialised construction and corrosion protection products.

Distribution facilities nationwide

Western Cape +27 (0)21 535 4455 **Eastern Cape** +27 (0)41 451 3944

**Gauteng** +27 (0)11 822 7242 **KwaZulu-Natal** +27 (0)31 705 7733







## **HEALTH AND SAFETY**

The system is solvent-free and non-flammable but may be hazardous during mixing and application.

Please read Safety Data Sheet and specific health and safety data for this product provided in compliance with the requirements of OHSA No.85 of 1993. The finished system is not hazardous to health or the environment.

## **WARRANTY**

Technical Finishes products are manufactured under high quality standards and are warranted against defective materials and are sold subject to standard Terms and Conditions of Sale, copies of which can be obtained upon request. Technical Finishes deals with approved applicators and carry a back to back warranty with these clients. Technical Finishes cannot be held responsible for the workmanship in surface preparation and application of our products, it is understood that the approved contractor will guarantee such workmanship and application. It is vital that the application is done in accordance to our specification.

Leading manufactures of specialist epoxy and polyurethane flooring systems, specialised construction and corrosion protection products.

Distribution facilities nationwide

Western Cape +27 (0)21 535 4455 **Eastern Cape** +27 (0)41 451 3944

**Gauteng** +27 (0)11 822 7242 **KwaZulu-Natal** +27 (0)31 705 7733







Technical Finishes products are manufactured under high

quality standards and are warranted against defective

materials and are sold subject to standard Terms and Conditions of Sale, copies of which can be obtained

upon request. Technical Finishes deals with approved applicators and carry a back to back warranty with these clients. Technical Finishes cannot be held responsible for

the workmanship in surface preparation and application of

our products, it is understood that the approved contractor will guarantee such workmanship and application. It

is vital that the application is done in accordance to our

specification.

## **APPLICATIONS:**

Bullet

## **SUBSTRATE REQUIREMENTS**

Text

#### **PREPARATION**

Text

## **PRIMING**

Text

Less than 5% Prime with either:

Text

Greater than 5% Text

Text

## **INSTALLATION:**

Text

Mixing

Text

**Placing** 

Text

#### **SEALING**

Text

Sealing specifications include:

Retail High Traffic: Text

**Commercial Foot Traffic: Text** 

Residential: Text

#### **MAINTENANCE**

Text

## **HEALTH AND SAFETY**

Please read Safety Data Sheet and specific health and safety data for this product provided in compliance with the requirements of OHSA No.85 of 1993. The finished system is not hazardous to health or the environment.

#### **WARRANTY**

Leading manufactures of specialist epoxy and polyurethane flooring systems, specialised construction and corrosion protection products.

Distribution facilities nationwide

Western Cape +27 (0)21 535 4455 **Eastern Cape** +27 (0)41 451 3944

**Gauteng** +27 (0)11 822 7242 KwaZulu-Natal +27 (0)31 705 7733





