



TECHNISHEEN ACRYLIC TOP COAT

DESCRIPTION

TECHNISHEEN is a tough, durable, interior or exterior, high build pure acrylic wall coating. The formulation is designed for excellent durability and waterproofing properties. Based on the highest grade pure acrylic emulsion Technisheen has excellent ultra violet resistant properties ensuring extended life even under exacting environment conditions.

APPLICATIONS

Protective waterproof coating for a variety of substrates including: Masonry, Plaster, Fibreboard, Wood, Galvanised surfaces. Ideal for new or previously painted surfaces such as food and beverage processing areas, office blocks, flats, schools, homes, hospitals, factories and hotels.

ADVANTAGES

- Single pack
- No volatile solvents
- Excellent ultraviolet light resistance
- Excellent hiding power
- Non yellowing and good stain resistance
- Thermoplastic and will not brittle.
- Very low dirt retention and easy cleaning
- Low water up take

Health and safety: This system is non-hazardous to health and environment. Please consult Health and Safety Data sheets for each product.

Technical Finishes products are guaranteed against defective materials and are manufactured under high quality standards and are sold subject to its standard Terms and Conditions of Sale, copies of which can be obtained on request.

TECHNICAL DETAILS

The figures that follow are typical properties achieved in laboratory tests at 20°C and at 50% Relative Humidity

Components	Single Pack
Drying Time	1- 2hrs
Service	6 hours
Full Cure	7 days
Over Coat Time	Min 2hrs
Coverage	: ± 8-10sqm /ℓ
Cleaning	Water
Colour	Various
No of Coats	2 Coats dependent on substrate

DIRECTIONS

All surfaces to be clean, sound and dry. All existing paint surfaces to be thoroughly washed with detergent to remove any dirt. Stiff bristle or wire brushes are used to remove flaking or peeling paint and oxidation products.

APPLICATION:

Apply by brush, mohair roller or airless spray.