

SOLIDWEAR HP 800

Advanced High-Performance Wearing Compound

A superior, quick-set, high-performance, technically advanced wearing compound using Novalac resin technology for superior temperature, chemical, and wear resistance.

It contains graded, high-density ceramic fillers, creating dense ceramic layers for excellent wear resistance, impact resistance and chemical resistance. It is ideal for protecting high wearing areas processing acid slurries. Also suitable in chrome reduction plants.

UNIQUE PRODUCT BENEFITS

- Excellent acid (up to 60% sulphuric acid) and alkali resistance.
- Extends life of costly plant and components.
- Easy to mix and apply.
- It conforms and spreads easily into tight corners and curved surfaces.
- Can be applied to vertical and overhead surfaces and areas in which compound shapes or difficult access makes the application of other wearing materials impractical.
- Water smoothable – lightly wetting trowel or gloved hand gives a smooth finish.
- Rapid cure - normally ready to use in 18 hours hours at 25°C - less if heat is applied.
- Excellent adhesion to metal and other surfaces under adverse conditions including damp surfaces.
- Good low temperature cure down to 5°C.
- Excellent corrosion resistance.

TECHNICAL DETAILS

Compressive Strength	110 MPa	ASTM D695-54
Tensile Strength	35 MPa	
Lap Shear	> 13 MPa	
Hardness	90	Shore D
Heat Deflection Temperature	90°C	
Chemical Resistance	Dilute acids and alkalis, aliphatic solvents and petroleum products, seawater and distilled water	
No. of Components	2	
Coverage @ 4.5 mm	1 m ²	
Mix Ratio	2 : 1 (by volume)	
Pot Life (500 ml)	25 min. @ 25°C	
Working Time	35 min.	
Practical Cure	2 to 3 hrs	
Full Cure	18 hrs	
Application	Trowel or gloved hand	
Application Temperature	5 to 35°C	
Shelf Life (on storage at 25°C)	12 months	

PACKAGING

Solidwear HP 800 is supplied as a 10 kg kit.

Leading manufacturers of specialist epoxy and polyurethane flooring systems, specialised construction and corrosion protection products.

Distribution facilities nationwide

Western Cape

+27 (0)21 535 4455

Eastern Cape

+27 (0)41 451 3944

Gauteng

+27 (0)11 822 7242

KwaZulu-Natal

+27 (0)31 705 7733



InfoTF@saint-gobain.com • www.technicalfinishes.com



TECHNICAL FINISHES
SPECIALIST FLOORING AND CONSTRUCTION SOLUTIONS

APPLICATIONS:

Any plant and equipment subject to erosion caused by abrasion from process materials.

Common areas of application are:

- feed chutes
- spigots
- pipe elbows
- slurry lines
- hoppers
- chutes
- settling tanks
- cyclones
- pump casings

SUBSTRATE REQUIREMENTS

All surfaces must be clean, dry and free of rust or mill scale. Grit blasting to SA 2½ is recommended. If mechanical grinding is used, ensure that the prepared surface has a rough profile.

INSTALLATION:

Using a steel trowel or gloved hand apply compound at 4 to 6 mm thickness or as specified.

Wipe smooth with hands, which are slightly wet with soapy water.

Any mixed material will become unusable after 40 minutes.

To accelerate curing time post cure, after compound has hardened, heat to about 40°C for 30 minutes.

HEALTH AND SAFETY

Ensure adequate ventilation in work area. Use protective clothing to avoid skin contact with uncured compound at all times. No sparks or naked flame to be permitted in the vicinity while tools and equipment are being cleaned with Epoxy Thinners or other flammable products.

Please read Safety Data Sheet and specific health and safety data for this product provided in compliance with the requirements of OHSA No.85 of 1993. The finished system is not hazardous to health or the environment.

WARRANTY

Technical Finishes products are manufactured under high quality standards and are warranted against defective materials and are sold subject to standard Terms and Conditions of Sale, copies of which can be obtained upon request. Technical Finishes deals with approved applicators and carry a back-to-back warranty with these clients. Technical Finishes cannot be held responsible for the workmanship in surface preparation and application of our products, it is understood that the approved contractor will guarantee such workmanship and application. It is vital that the application is done in accordance to our specification.

**Leading manufacturers of specialist epoxy and polyurethane flooring systems,
specialised construction and corrosion protection products.**

Distribution facilities nationwide

Western Cape
+27 (0)21 535 4455

Eastern Cape
+27 (0)41 451 3944

Gauteng
+27 (0)11 822 7242

KwaZulu-Natal
+27 (0)31 705 7733



InfoTF@saint-gobain.com • www.technicalfinishes.com



TECHNICAL FINISHES
SPECIALIST FLOORING AND CONSTRUCTION SOLUTIONS